

EASY-LOAD DESKTOP THERMAL

POS PRINTER

SLK-TL100

- Compact & Unique design : excellent design with small size and low height.
- Front Paper exit
- Spill-proof function : superior resistance to spill with a sealed top.
- High speed printing : 200mm/sec
- Paper width : 80mm
- ESC/POS command compatible
- Easy to use & Innovative



INTERFACE






COVER OPEN



SPECIFICATION

ITEM	TYPE	
MODEL	SLK-TL100	
PRINTING	METHOD	Direct Thermal
	SPEED	200mm/sec
	WIDTH	72mm(512Dots/Line)
	RESOLUTION	180DPI
PAPER	TYPE	Thermal Paper
	WIDTH	80mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. ϕ 80mm
	ROLL CORE INNER	12.5mm \pm 0.5mm
RELIABILITY	TPH LIFE	160km
	MCBF	60,000,000Lines
AUTO CUTTER	1,500,000cuts(Guillotine)	
SENSOR	Paper End, Paper Low, Cover Open, Black Mark Sensor(Optional)	
INTERFACE	USB, Serial	
EMULATION	ESC/POS Command Compatible	
DRIVER	Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK	
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 2.5A
TEMPERATURE	OPERATION	0 ~ 45°C
	STORAGE	-20 ~ 60°C
DIMENSION	136 x 165 x 111 mm (W x D x H)	
WEIGHT	0.6kg	





● SPECIFICATION

ITEM		TYPE
MODEL		LK-TL100
PRINTING	METHOD	Direct Thermal
	SPEED	200mm/sec
	WIDTH	72mm(512Dots/Line)
	RESOLUTION	180DPI
PAPER	TYPE	Thermal Paper
	WIDTH	80mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. ø 80mm
	ROLL CORE INNER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	160km
	MCBF	60,000,000Lines
AUTO CUTTER		1,500,000cuts(Guillotine)
SENSOR		Paper End, Paper Low, Cover Open, Black Mark Sensor(Optional)
INTERFACE		USB, Serial
EMULATION		ESC/POS Command Compatible
DRIVER		Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 2.5A
TEMPERATURE	OPERATION	5 ~ 40°C
	STORAGE	-20 ~ 60°C
DIMENSION		136 x 165 x 111 mm (W x D x H)
WEIGHT		0.6kg

INTERFACE



COVER OPEN



SEWOO TECH Co., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do,
Korea 447-210

T +82-31-459-8200 F +82-31-459-8880 www.miniprinter.com